



Nahtlose Rohre

seamless tubes

EN 10216-5 · Abnahmeprüfzeugnis 3.1 bzw. 3.1 AD-W2 / W10 · Herstellungslänge 4 - 7 m

EN 10216-5 · inspection certificate 3.1 respectively 3.1 AD-W2 / W10 · random lengths 4 - 7 m

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
4,00 x 1,00	0,075	•	•	•		
5,00 x 1,00	0,100	•	•	•		
6,00 x 0,50	0,069	•				
1,00	0,125	•	•	•	•	
1,50	0,169	•	•	•		
2,00	0,200	•	•	•		
7,00 x 1,00	0,069	•		•		
8,00 x 0,50	0,094	•		•		
1,00	0,175	•	•	•	•	
1,50	0,244	•	•	•	•	
2,00	0,300	•	•	•		
2,50	0,344	•	•	•		
9,00 x 1,00	0,200	•		•		
10,00 x 1,00	0,225	•	•	•	•	
1,50	0,319	•	•	•	•	
2,00	0,401	•	•	•	•	
2,50	0,470	•		•		
3,00	0,526		•	•		
10,20 x 1,60	0,345	•			•	
2,00	0,411	•	•	•	•	
11,00 x 1,50	0,357		•			
12,00 x 1,00	0,275	•	•	•	•	
0,50	0,394	•	•	•		
2,00	0,501	•	•	•	•	
2,50	0,595	•	•	•		
3,00	0,676	•	•	•		
4,00	0,801		•	•		
13,00 x 1,00	0,300	•				
1,50	0,432	•				
2,50	0,657	•				
13,50 x 1,60	0,477	•			•	
2,00	0,576	•				
2,30	0,645	•	•	•	•	
2,60	0,710		•	•		
2,90	0,770		•	•		
13,72 x 1,65	0,498	•				
2,24	0,644	•				
1/4" SCH 10S						
3,02	0,809	•				
1/4" SCH 40S						
14,00 x 1,00	0,326	•	•	•	•	
1,50	0,470	•	•	•		
2,00	0,601	•	•	•	•	
2,50	0,720	•	•	•		
3,00	0,826	•	•	•		

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
15,00 x 1,00	0,351	•	•	•		
1,50	0,507	•	•	•	•	
2,00	0,651	•	•	•		
2,50	0,783		•	•		
3,00	0,901	•	•	•		
4,00	1,102		•	•		
16,00 x 1,00	0,376	•	•	•		
1,50	0,545	•	•	•	•	
2,00	0,701	•	•	•	•	
2,50	0,845	•	•	•		
3,00	0,976	•	•	•		
3,50	1,096		•	•		
4,00	1,202	•	•	•		
5,00	1,378		•	•		
17,00 x 1,00	0,401	•	•	•		
1,50	0,582	•		•		
3,00	1,052	•	•	•		
17,14 x 2,31	0,858	•				
3/8" SCH 40S						
3,20	1,117	•				
3/8" SCH 80S						
17,20 x 1,60	0,625	•	•	•	•	
2,00	0,761	•	•	•		
2,30	0,858	•	•	•	•	
2,90	1,038		•	•		
3,20	1,122		•	•		
18,00 x 1,00	0,426	•	•	•		
1,50	0,620	•	•	•	•	
2,00	0,801	•	•	•		
2,50	0,970	•	•	•		
3,00	1,127	•	•	•		
3,50	1,271		•	•		
4,00	1,402	•	•	•		
20,00 x 1,00	0,476	•	•	•		
1,50	0,695	•	•	•	•	
2,00	0,901	•	•	•	•	
2,50	1,096	•	•	•	•	
3,00	1,277	•	•	•		
3,50	1,446		•	•		
4,00	1,603	•	•	•	•	
5,00	1,878	•	•	•		
21,00 x 3,00	1,352	•				
21,30 x 1,60	0,789	•	•	•	•	
2,00	0,967	•	•	•	•	
2,60	1,217	•	•	•	•	
2,90	1,336	•	•	•		
3,20	1,450	•	•	•		



Nahtlose Rohre

seamless tubes

EN 10216-5 · Abnahmeprüfzeugnis 3.1 bzw. 3.1 AD-W2 / W10 · Herstellungslänge 4 - 7 m

EN 10216-5 · inspection certificate 3.1 respectively 3.1 AD-W2 / W10 · random lengths 4 - 7 m

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
21,34 x 2,11 1/2" SCH 10S	1,016	•	•	•		
2,77 1/2" SCH 40S	1,288	•	•		•	•
3,73 1/2" SCH 80S	1,645	•	•		•	•
4,75 1/2" SCH 160S	1,645		•	•		
22,00 x 1,00	0,526	•	•	•		
1,50	0,770	•	•	•	•	
2,00	1,002	•	•	•		
2,50	1,221	•	•	•		
3,00	1,427	•	•	•		
4,00	1,803	•	•	•		
23,00 x 1,50	0,808	•	•	•	•	
2,00	1,051	•		•		
4,00	1,903					
24,00 x 2,00	1,102	•	•	•	•	
3,50	1,797		•	•		
4,00	2,003	•	•	•		
25,00 x 1,00	0,601	•	•	•		
1,50	0,883	•	•	•	•	
2,00	1,152	•	•	•	•	
2,50	1,409	•	•	•	•	
3,00	1,605	•	•	•		
3,50	1,884		•	•		
4,00	2,103	•	•	•		
5,00	2,504	•	•	•		
6,00	2,855		•	•		
26,67 x 2,11 3/4" SCH 10S	1,298	•	•			•
2,87 3/4" SCH 40S	1,710	•	•			•
3,91 3/4" SCH 80S	2,228	•	•			•
5,54 3/4" SCH 160S	2,931		•	•		
26,90 x 1,60	1,043	•		•	•	
2,00	1,247	•	•	•	•	
2,30	1,417		•	•		
2,60	1,582	•	•	•	•	
2,90	1,582		•	•	•	
3,20	1,899	•	•	•	•	
4,00	2,293	•	•	•		
27,00 x 3,00	1,803	•				
4,00	2,304	•	•			

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
28,00 x 1,00	0,767	•	•	•		
1,50	0,995	•	•	•	•	
2,00	1,302	•	•	•	•	
2,50	1,596	•	•	•		
3,00	1,878		•	•		
3,50	2,117		•	•		
4,00	2,403		•	•		
5,00	2,880	•	•	•		
30,00 x 1,00	0,726	•	•	•		
1,50	1,070	•	•	•		
2,00	1,402	•	•	•		
2,50	1,721	•	•	•	•	
2,60	1,784	•	•	•		
3,00	2,028	•	•	•	•	
3,50	2,320	•	•	•		
4,00	2,604		•	•		
5,00	3,130	•	•	•		
32,00 x 1,50	1,146	•				
2,00	1,502	•	•	•	•	
2,50	1,847	•	•	•		
3,00	2,178	•	•	•		
3,50	2,438	•		•		
4,00	2,804		•	•		
33,00 x 1,50	1,183	•	•	•		
4,00	2,905	•				
33,40 x 2,77 1" SCH 10S	2,125	•	•			•
3,38 1" SCH 40S	2,541	•	•			•
4,55 1" SCH 80S	3,287	•	•			•
6,35 1" SCH 160S	4,301	•	•	•		
33,70 x 1,60	1,324	•	•		•	
2,00	1,588	•	•	•	•	
2,60	2,025	•	•	•	•	
2,90	2,237	•	•	•		
3,20	2,444	•	•	•	•	
3,60	2,713		•	•		
4,05	3,007	•	•	•		
4,50	3,290		•	•		
5,00	3,593	•	•	•		
34,00 x 1,50	1,221	•		•		
2,00	1,603	•		•		
3,50	2,673		•	•		
4,00	3,005	•	•	•		
5,00	3,631		•	•		
5,50	3,925		•	•		

Nahtlose Rohre

seamless tubes



EN 10216-5 · Abnahmeprüfzeugnis 3.1 bzw. 3.1 AD-W2 / W10 · Herstellungslänge 4 - 7 m

EN 10216-5 · inspection certificate 3.1 respectively 3.1 AD-W2 / W10 · random lengths 4 - 7 m

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
35,00 x 1,50	1,258	•	•	•		
2,00	1,653	•	•	•	•	
2,50	2,035	•	•	•		
3,00	2,404		•	•		
4,00	3,105	•				
5,00	3,756		•	•		
36,00 x 2,00	1,703	•		•		
38,00 x 1,50	1,371	•	•	•		
2,00	1,803	•	•	•	•	
2,50	2,222	•	•	•		
2,60	2,305	•	•	•	•	
3,00	2,629	•	•	•	•	
3,60	3,101		•	•		
4,00	3,405	•	•	•		
4,50	3,775			•		
5,00	4,132	•	•	•		
6,00	4,808		•	•		
6,30	5,000	•		•		
40,00 x 1,50	1,446	•	•	•		
2,00	1,903	•	•	•	•	
2,50	2,348	•	•	•		
3,00	2,779	•	•	•		
4,00	3,606	•	•	•		
5,00	4,382	•	•	•	•	
42,00 x 2,00	2,003	•	•	•		
3,00	2,930	•	•	•		
6,00	5,409	•	•	•		
42,16 x 2,77	2,732	•	•			•
1 ¼" SCH 10S	3,56	•	•	•		
1 ¼" SCH 40S	4,85	•	•	•		
1 ¼" SCH 80S	6,35	•	•	•		
1 ¼" SCH 160S	5,694	•	•	•		
42,40 x 1,60	1,635	•	•	•		
2,00	2,023	•	•	•	•	
2,60	2,591	•	•	•	•	
2,90	2,868		•	•		
3,20	3,141	•	•	•	•	
3,60	3,498		•	•		
4,05	3,889	•	•	•		
4,50	4,270	•				
43,00 x 1,50	1,559	•		•		
5,50	5,165		•	•		
44,00 x 2,00	2,103	•				
44,50 x 2,00	2,128	•	•	•		
2,60	2,728	•	•	•	•	
2,90	3,021	•	•	•		
4,00	4,056	•	•	•		
5,50	5,371	•				

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
45,00 x 1,60	1,733	•				
2,00	2,153	•				
3,00	3,155		•	•		
3,50	3,637		•	•		
5,00	5,008		•	•		
48,00 x 4,00	4,407	•				
48,26 x 2,77	3,155	•	•			•
1 ½" SCH 10S	3,68	•	•	•		•
1 ½" SCH 40S	5,08	•	•			•
1 ½" SCH 80S	7,14	•	•	•		
1 ½" SCH 160S	7,352	•	•	•		
48,30 x 1,60	1,871	•		•		
2,00	2,319	•	•	•	•	
2,60	2,975	•	•	•	•	
2,90	3,297		•	•		
3,20	3,614	•	•	•	•	
3,60	4,029	•	•	•	•	
4,05	4,487	•	•	•	•	
5,00	5,421		•	•		
6,30	6,626	•	•	•		
8,00	8,072	•	•	•		
49,00 x 5,50	5,991		•	•		
50,00 x 1,50	1,822	•				
2,00	2,404	•	•	•	•	
2,50	2,974	•				
3,00	3,531	•	•	•		
4,00	4,607	•	•	•		
5,00	5,634	•	•	•	•	
6,00	6,611	•	•	•		
51,00 x 2,00	2,454	•		•		
2,60	3,151	•	•	•		
4,00	4,708		•			
52,00 x 1,50	1,897	•	•	•		
2,00	2,504	•				
4,00	4,804		•			
53,00 x 1,50	1,934	•	•	•		
3,00	3,756	•				
3,60	4,453	•				
4,00	4,908		•			
4,50	5,465		•			
54,00 x 2,00	2,604	•	•	•	•	
55,00 x 2,50	3,287	•		•	•	
5,00	6,260	•		•	•	



Nahtlose Rohre

seamless tubes

EN 10216-5 · Abnahmeprüfzeugnis 3.1 bzw. 3.1 AD-W2 / W10 · Herstellungslänge 4 - 7 m

EN 10216-5 · inspection certificate 3.1 respectively 3.1 AD-W2 / W10 · random lengths 4 - 7 m

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
57,00 x 2,00	2,754	•	•	•		
2,60	3,542	•	•	•	•	
2,90	3,929	•	•	•		•
3,50	4,689		•	•		
4,00	5,308	•	•	•		
4,50	5,916		•	•		
5,00	6,510		•	•		
6,50	8,219	•	•	•		
60,00 x 5,00	6,886	•	•	•		
60,30 x 1,60	2,352	•	•	•		
2,00	2,920	•	•	•	•	
2,60	3,757	•	•	•	•	
2,77	3,990	•	•	•		•
2" SCH 10S						
2,90	4,168	•	•	•	•	
3,00	4,304	•	•	•		
3,20	4,575	•	•	•		
3,60	5,111	•	•	•	•	•
3,91	5,521	•	•			
2" SCH 40S						
4,00	5,639		•	•		
4,50	6,228	•	•	•		
5,00	6,923		•	•		•
5,54	7,596	•	•			
2" SCH 80S						
6,30	8,519		•	•		
8,00	10,477	•	•	•		
8,74	11,283		•	•		
2" SCH160S						
10,00	12,585	•				
63,50 x 2,50	3,662		•	•		
2,60	3,965		•	•		
5,00	7,324		•	•		
64,00 x 2,00	3,105	•		•		
65,00 x 2,50	3,913		•			
3,00	4,657		•	•		
3,50	5,390		•	•		
68,00 x 4,00	6,410	•				
70,00 x 2,00	3,405	•	•	•		
2,90	4,873	•	•	•	•	
3,00	5,033	•				
4,00	6,611	•	•	•		
4,50	7,381		•	•	•	
5,00	8,138	•	•	•		
6,30	10,048		•	•		
7,00	11,043		•	•		
73,03 x 3,05	5,344					•
73,03 x 5,16	8,769	•	•			•
2½" SCH 40 S						
7,01	11,588	•				
2 ½" SCH80S						

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
75,00 x 2,50	4,539	•				
76,00 x 5,00	8,889	•	•	•		
6,00	10,517	•	•	•		
76,10 x 2,00	3,711	•	•	•		
2,30	4,250		•	•		
2,60	4,785	•	•	•	•	
2,90	5,315	•	•	•	•	•
3,20	5,841	•	•	•		
3,60	6,535	•	•	•	•	
4,00	7,222		•	•		
4,50	8,068	•	•	•		
5,00	8,901		•	•		
6,30	11,011		•	•		
7,10	12,267		•	•		
8,00	13,641		•	•		
10,00	16,551		•	•		
12,50	19,900	•	•	•		
80,00 x 2,00	3,90	•	•	•		
2,50	4,852	•				
4,00	7,612	•	•	•		
5,00	9,390	•	•	•		
82,50 x 3,60	7,112		•	•		
85,00 x 2,50	5,165		•			
88,90 x 2,00	4,352	•	•	•		
2,30	4,987		•	•		
2,60	5,409	•	•	•	•	
2,90	6,245	•	•	•		
3,05	6,557	•	•			•
3" SCH 10S						
3,20	6,867	•	•	•	•	
3,60	7,689	•	•	•		
4,05	8,605	•	•	•	•	
4,50	9,510	•	•	•		
5,00	10,504		•	•		
5,49	11,466	•	•			•
3" SCH 40S						
5,60	11,680		•	•		
6,30	13,030		•	•		
7,62	15,509	•	•			•
3" SCH 80S						
10,00	19,756			•		
11,13	21,674			•		
3" SCH169S						
90,00 x 5,00	10,642		•	•		
97,00 x 4,00	9,315		•	•		
100,00 x 3,00	7,287		•	•		
5,00	11,894		•	•		

Nahtlose Rohre

seamless tubes



EN 10216-5 · Abnahmeprüfzeugnis 3.1 bzw. 3.1 AD-W2 / W10 · Herstellungslänge 4 - 7 m

EN 10216-5 · inspection certificate 3.1 respectively 3.1 AD-W2 / W10 · random lengths 4 - 7 m

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
101,60 x 3,05	7,526	•	•	•		
3,60	8,832	•	•	•		
4,05	9,893	•	•	•		
5,00	12,094		•	•		
5,74	13,778	•	•	•		
6,30	15,053	•	•	•		
3 ½" SCH 40S						
8,08	18,921	•				
3 ½" SCH 80S						
102,00 x 6,50	15,544	•	•	•		
105,00 x 2,50	6,417		•			
108,00 x 3,00	7,888	•	•	•		
3,20	8,397		•	•		
3,60	9,411	•	•	•		
4,00	10,417	•	•	•	•	
4,50	11,662		•	•		
5,00	12,896		•	•		
6,30	16,043		•	•		
8,00	20,032		•	•		
114,30 x 2,60	7,272	•	•	•		
3,05	8,496	•	•			•
4" SCH 10S						
3,20	8,902		•	•		
3,60	9,979	•	•	•		
4,00	11,047		•	•		
4,50	12,372	•	•	•	•	
5,00	13,684		•	•		
5,40	14,725		•	•		
6,02	16,322	•	•			•
4" SCH 40S						
6,30	17,037		•	•		
7,10	19,058	•	•	•		
8,56	22,665	•	•	•		
4" SCH 80S						
11,13	28,752	•	•	•		
13,49	34,052	•	•	•		
14,70	35,592	•	•	•		
20,00	47,235	•	•	•		
121,00 x 4,00	11,719		•	•		
127,00 x 4,00	12,320		•	•		
133,00 x 4,00	12,921	•	•	•	•	
5,00	16,026		•	•	•	
6,30	19,987		•	•		
139,70 x 4,00	13,592	•	•	•		
5,00	16,860		•	•		
6,30	21,044	•	•	•		
7,10	23,574		•	•		

Abmessung dimension in mm	Gewicht weight kg/m	W.-Nr. / material				
		4301/4306	4541	4571	4435	4462
141,30 x 6,55	22,101		•			•
5" SCH 40S						
9,53	31,444		•	•		
5" SCH 80S						
159,00 x 4,50	17,409	•	•	•		
5,00	19,281			•		
6,30	24,089	•	•	•		
7,10	27,005		•	•		
168,30 x 3,40	14,038	•				
3,45	14,241					•
4,50	18,457		•	•		
5,00	20,445	•	•	•		
6,30	25,556		•	•		
7,11	28,690	•	•			•
6" SCH 40S						
10,97	43,210		•			•
6" SCH 80S						
219,10 x 3,76	20,274	•				
6,30	33,569	•	•	•		
8,18	43,200		•			•
8" SCH 40S						
10,00	52,359		•	•		
12,70	66,020		•	•		
8" SCH 80S						
273,05 x 9,27	64,100	•				
12,70	82,200	•				
323,85 x 10,31	80,940	•				
12,70	98,940	•				
323,90 x 9,52	74,943	•				
10,31	80,994	•				
12,70	98,948	•				